



	SIZE	LI/SS	SECTION WIDTH (mm)	RIM STANDARD	OD(mm)	UTQG	MAXLOAD	MAX PRESSURE	SIDEW ALL
1	265/65R17LT	120/117S	272	8J	776	500AB	1400/1285	300/44	OWL
2	265/70R17LT	112/109S	272	8J	804	500AB	1450/1320	300/44	OWL
3	285/70R17LT	116/113Q	292	8J	832	500AB	1450/1320	550/80	OWL
4	265/60R18LT	119/116S	272	8J	775	420AA	1360/1250	300/44	BSW
5	265/70R16LT	121/118S	272	8J	778	500AB	1450/1320	300/44	OWL
6	245/70R16LT	113/110S	248	7J	750	500AB	1150/1060	300/44	OWL
7	31×10.50R15LT	109S	268	8 1/2J	775	500AB	1030	350/51	OWL
8	265/75R16LT	123/120R	267	7 1/2J	804	500AB	1550/1400	550/80	OWL
9	245/65R17LT	111/108S	248	7J	750	500AB	925/850	300/44	OWL
10	225/65R17LT	107/103S	228	6 1/2J	724	420AA	975/875	300/44	OWL
11	235/70R16LT	104/101S	240	7J	736	500AB	900/825	300/44	OWL
12	245/75R16LT	120/116S	248	7J	774	500AB	1380/1260	550/80	OWL
13	215/70R16LT	100/97R	221	6 1/2J	708	500AB	800/730	300/44	OWL
14	285/75R16LT	126/123R	286	8J	834	500AB	1700/1550	550/80	OWL
15	315/70R17LT	113/110S	318	10J	877	500AB	1450/1320	450/65	OWL
16	275/65R18LT	123/120R	279	8J	815	500AB	1550/1400	300/44	BSW
17	265/50R20LT	116/113R	277	8 1/2J	774	500AB	1180/1060	300/50	BSW
18	275/55R20LT	115/112S	284	8 1/2J	810	500AB	1215/1120	300/50	BSW
19	255/70R18LT	119/116Q	260	7 1/2J	763	500AB	1360/1250	300/50	BSW
20	265/65R18LT	122/119R	272	8J	775	420AA	1500/1360	300/44	BSW
21	265/70R18LT	124/121R	277	8J	829	420AA	1600/1450	300/44	BSW
22	35×12.50R18LT	123R	318	10J	826	500AB	1550	450/65	BSW
23	265/60R20LT	121/118S	277	8 1/2J	774	500AB	1180/1060	450/65	BSW
24	275/60R20LT	119/116S	284	8 1/2J	748	500AB	1180/1060	550/80	BSW
25	275/65R20LT	126/123S	284	8 1/2J	810	500AB	1215/1120	450/65	BSW
26	285/50R20LT	122/119S	297	9J	794	500AB	1360/1250	550/80	BSW
27	285/60R20LT	125/122S	297	9J	828	500AB	1500/1360	550/80	BSW
28	245/70R17LT	119/116S	248	7J	776	500AB	1360/1250	550/80	OWL
29	245/75R17LT	121/118S	248	7J	780	500AB	1360/1250	550/80	OWL
30	255/65R17LT	114/110S	260	7 1/2J	764	500AB	1180/1060	450/65	OWL
31	275/65R17LT	121/118S	279	8J	790	500AB	1450/1320	550/80	OWL



	SIZE	LI/SS	SECTION WIDTH (mm)	RIM STANDARD	OD(mm)	UTQG	MAXLOAD	MAX PRESSURE	SIDEW ALL
1	LT235/75R15	104/101S	235	6 1/2J	733	500AB	900/825	350/50	OWL
2	LT31X10.50R15	109S	268	8 1/2J	775	500AA	1030	350/51	OWL
3	P215/75R15	100T	216	6J	703	500AB	800/730	350/50	OWL
4	P225/75R15	102T	228	6J	744	500AA	1215	550/80	OWL
5	P235/75R15	109SXL	235	6 1/2J	733	500AA	900/825	350/50	OWL
6	LT225/75R16	115/112S	228	6J	726	500AA	1215	550/80	OWL
7	LT235/85R16	120/116S	240	6 1/2J	806	500AA	1380/1260	550/80	OWL
8	LT245/75R16	120/116S	248	7J	774	500AA	1380/1260	550/80	OWL
9	LT265/75R16	123/120S	267	7 1/2J	804	500AA	1550/1400	550/80	OWL
10	P215/70R16	100T	221	6 1/2J	708	500AA	800/730	300/44	OWL
11	P225/70R16	103T	228	6 1/2J	722	500AA	850/775	350/50	OWL
12	P235/70R16	106T	240	7J	736	500AA	900/825	300/44	OWL
13	P245/70R16	107T	248	7J	750	500AB	1150/1060	300/44	OWL
14	P255/70R16	111T	262	7J	765	500AA	1500	550/80	OWL
15	P265/70R16	112T	272	8J	778	500AB	1450/1320	300/44	OWL
16	LT245/75R17	121/118S	248	7J	780	500AA	1360/1250	550/80	OWL
17	LT265/70R17	121/118S	272	8J	804	500AA	1450/1320	300/44	OWL
18	P235/65R17	104T	240	7J	738	500AA	1030	450/65	OWL
19	P245/65R17	107T	248	7J	750	500AA	925/850	300/44	OWL
20	P265/65R17	112T	272	8j	776	420AA	1400/1285	300/44	OWL
21	P265/70R17	115T	272	8J	804	420AA	1450/1320	300/44	OWL



Shandong Wideway Tire Co., Ltd

Website: www.widewaytire.com

Tel: 0086-532-67790851

Fax: 0086-532-67790852

Address: No.66 Tokyo Road, Free Trade Zone, Qingdao, Shandong, China